| SPECIFICATIONS | MW826ST | | |
|---------------------------------------|---|--|--------------|
| Projection System | DLP® | | |
| Native Resolution | WXGA, 1280x800 | | |
| Brightness | 3400AL | | |
| Contrast Ratio | 20000:1 | | |
| Display Color | 1.07 Billion Colors | | |
| Lens | F/#=2.6 ; f=6.9 mm | | |
| Aspect Ratio | Native 16:10 (5 aspect ratio selectable) | | |
| Throw Ratio | 0.49 | | |
| Clear Image Size / Maximum Image Size | 60"~120" / 120" Fixed | | |
| Zoom Ratio Lamp Type | 200W | | |
| Lamp Mode | | | |
| (Normal/Eco/SmartEco/LampSave) | 5000/10000/10000/15000 hours* | | |
| Keystone Adjustment | 1D, Vertical +/- 30 degrees | | |
| Projection Offset | 105% | | |
| Resolution Support | VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking" | | |
| Horizontal Frequency | 15K~102KHz | | |
| Vertical Scan Rate | 23~120Hz | | |
| Compatibility | HDTV Compatibility | 480i, 480p, 576i, 567p, 720p, 1080i, 1080p | |
| | 3D Compatibility (Please refer to User's Manual for detailed support timing.)" | Frame Sequential: Up to 720p Frame Packing: Up to 24 Hz 1080p Side by Side Half: Up to 60Hz 1080p Top Bottom: Up to 60Hz 1080p | |
| Interface | Computer in (D-sub 15pin) | x 2 (Share with component) | |
| | Monitor out (D-sub 15pin) | x 1 | |
| | Composite Video in (RCA) | x 1 | |
| | S-Video in (Mini DIN 4pin) | x 1 | |
| | HDMI | x2 (1 share with MHL) | |
| | Audio in (Mini Jack) | x2 | |
| | | x 1 | |
| | Audio out (Mini Jack) | | |
| | Audio L/R in (RCA) | x1 | |
| | Speaker | 10Wx 1 | |
| | USB (Type A) | x1 (power only 5V/1.5A) | |
| | USB (Type Mini B) | x1 (Download & page/down) | |
| | RS232 (DB-9pin) | x 1 | |
| | LAN (RJ45) | x 1 | |
| | Dimensions(W x H x D) | 296 (W)*239(D)*120(H) mm | |
| Dimensions | Weight | | |
| | _ | 2.6 Kg (5.7 lbs) | |
| Power | Power Supply | AC 100 to 240 V, 50/60 Hz | |
| | Power Consumption | 260W(typical), Standby<0.5W, Network standby<2W | |
| Audible Noise (Normal/Eco) | 33/29 dBA (Normal/Eco mode) | | |
| On-Screen Display Languages | Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian / Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnam (30 languages) | | |
| Picture Modes | Bright / Presentation / sRGB / Cinema / (3D) / User 1 / User 2 | | |
| Accessories | Standard | Optional | |
| | Remote Control w/ Battery RCE013, RCE013J (for J sku) | PointWrite | PW02 |
| | Power Cord (by region) | FingerTouch | PT12 |
| | User Manual CD | Spare Lamp Kit | 5J.JGE05.001 |
| | Quick Start Guide | Wall Mount | WM06G3 |
| | Warranty Card (by region) | | |

MW826ST

Digital Projector

- SmartEco Power Saving Technology
- 0.49 Short Throw Ratio
- Designed for Education & IWB
- Blu-ray Full HD 3D support
- PointWrite Interactive Solution Compatible











- 296mm -

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

